



LASER BLAZER® GTD SERIES HIGH POWERED GREEN

For applications with bright lighting where standard lasers are hard to see, Connexus Industries provides a line of High Powered Green Laser Guidelines. The GTD

series project brilliant bright lines that operators can easily see and are equipped with TEC (thermal electric

cooling) which keeps the output power stable even in extreme temperatures.

Along with our Powerline® Lens, our Laser Blazer® Lasers deliver the sharpest quality laser lines in the industry. The entire laser line will be consistent in intensity and thickness.

Typical Applications:

- * OEM Industrial Equipment
- * Steel Plate Cutting
- * Sawmill Equipment: Grading Decks, Carriage, Log Cut-
- * Offs Furniture and Woodworking
- * Textile Processing
- * Stone Cutting: Bridge & Slab Saws
- * Machine Vision Camera, Scanning/ Optimizing
- * Medical: Alignment & Positioning
- *

High Powered Green Laser Benefits:

- * Higher Accuracy
- * Maximize Yield
- * Minimize Waste
- * Greater Productivity

LAHARCO® GREEN DIODE

- * Superior Line Quality * Specially Designed Optics * Rugged Construction * *
 Nickel Plated Finish * Full Warranty * 3-Day Repair Turnaround *

The new Laharco® self-contained assembly provides intense green light in 10-30mW power configurations. Operating from 5-24 VDC or 100-240 VDC TTL. These new diode pumped solid state lasers maintain constant output power.

The intense green beam is useful for visual and machine vision applications in harsh or industrial environments, with optics housed in a sealed cell to provide added protection against contaminants and moisture.

Features:

- * Power Stability better than $\pm 5\%$ over 8 hours
- * TEC (thermal electric cooling) provides wide operating temperature range
- * Rugged Industrial Packaging
- * One piece housing entirely self-contained 12 Month Warranty from date of Shipment Warm up time <5 minutes
- * Bore Sighted Beam
- * Focused Beam for each Application

Specifications:

Wave Length	-----	532nm
Environmental	-----	Meets NEMA, Water Resistant
Beam Angle	-----	10 to 90 Degrees
Powers Available	-----	10-30mW
Operating Current	-----	1.5 Amp
Housing	-----	Aluminum - Nickel Plated
Dimensions	-----	Diameter 1-3/8" x Length 12"
Weight	-----	2 lbs
Operating Temperature	-----	-20C to +45C (-4F to 113F)
Operating Voltage	-----	5-24 VDC, 100 VAC to 240 VAC, 50Hz/60Hz (1.5 - 2.4 VDC TTL)
Output Mode	-----	Gaussian TEM00
Beam Profile	-----	1mm Round Bea 1/E2

